



FIBRE GLAST DEVELOPMENTS CORP.  
385 Carr Drive  
BROOKVILLE, OH 45309

TELEPHONE: (937) 833-5200  
FAX: (937) 833-6555  
**FOR CHEMICAL EMERGENCY  
CALL (800) 424-9300 24 HRS.**

---

## SECTION 1 - PRODUCT IDENTIFICATION

---

PRODUCT NAME: PART #1678 Stretchlon 200 Bagging Film

Hazardous Ratings: Health = 0 Fire = 0 Reactivity = 0  
(scale 0-4)

CAS#: None  
DOT Hazardous Class: None  
Proper Shipping Name: Plastics  
Personal Protection: None  
Technical Name: None

---

## SECTION 2 – HAZARDOUS INGREDIENTS

---

Ingredients: None  
CAS Number:  
Weight: %  
Exposure Limits: ACGIH/TLV  
OSHA PEL: mm HG

---

## SECTION 3 – PHYSICAL DATA

---

**Description:** Film, profiles, sheet and tubing. Has a very faint odor.  
**Boiling Range:** N/A  
**Vapor Density:** N/A  
**Water Solubility:** Insoluble  
**Evap. Rate (butyl acetate = 1):** N/A  
**Vapor Pressure (mm Hg):** N/A  
**Melting Point Range:** 100°C to 250°C  
**Specific Gravity:** 1.0-1.3

---

## SECTION 4 – FIRE AND EXPLOSION DATA

---

**Flash Point (D1929-CC):** >390°C (740°F)

**Flammable Limits:** LEL: N/A UEL: N/A

**Extinguishing media:**

Water, ABD dry chemicals, protein air foam.

**Special Fire Fighting Instructions:**

Wear NIOSH approved self-contained breathing apparatus. CO<sup>2</sup> extinguishers may be inadequate.

**Unusal Fire and Explosion Hazards:**

These polymers are combustibile when forced to burn and may emit toxic odors.

---

## SECTION 5 – HEALTH HAZARD DATA

---

**Permissible Exposure Level:**

N/E

**Primary Routes of Exposure:**

Processing vapors by inhalation: neither skin nor ingestion are known to be routes of exposure.

**EFFECTS OF OVEREXPOSURE:**

**Acute:** Heat processing at or above the decomposition point may release the products discussed in Section IV including the isocyanate MDI which may result in irritation of the respiratory tract and eyes, chest tightness, coughing, headache, and dyspnea. Sensitization with subsequent asthma like attacks may follow.

**Chronic:**

**Carcinogen status:** NTP: No IARC: No OSHA: No

**Signs and Symptoms of Exposures:**

Processing vapors above melting point may cause irritation of respiratory tract, eyes, and skin; processing temperatures at or above the decomposition point may release products including MDI which may cause irritation of the respiratory tract, eyes, skin, chest tightness, coughing, headache, and dyspnea.

**Medical Conditions Generally Aggravated by Exposure:**

None Known

**EMERGENCY AND FIRST AID PROCEDURE:**

**In Case of Inhalation:**

In case of inhalation of vapors, remove to fresh air. If breathing has stopped, restore breathing and get medical attention.

**In Case of Skin Contact:**

If hot, molten polyurethane contacts skin, flush immediately with water and seek medical attention for thermal burn.

---

## SECTION 6 – REACTIVITY DATA

---

**Stability:** Stable

**Incompatibilities:** None Known

**Hazardous decomposition:**

Carbon monoxide, carbon dioxide, oxides of nitrogen, hydrogen cyanide, aliphatic and aromatic hydrocarbons including MDI (methylene bisphenyl isocyanate) may be created during incomplete combustion.

**Hazardous polymerization:** Will not occur

**Conditions to avoid:** None known

---

## SECTION 7 – SPILL, LEAK, DISPOSAL PROCEDURE

---

**Steps to be taken in case material is released or spilled:**

Vacuum or sweep into a closed container for reuse or disposal.

**Waste disposal:**

Collect absorbent material into metal waste containers and dispose of in accordance with all local, state and federal hazardous waste regulations in a licensed landfill or by incineration.

**Other Precautions:**

None Known

---

## SECTION 8 – SPECIAL PROTECTION INFORMATION

---

**Ventilation:**

Local Exhaust – When melt processing to remove vapors exhaust hoods should maintain a minimum of 100 lfm face velocity.

**Respiratory Protection:**

For processing above the melting point, NIOSH approved, supplied air respirators should be used-not required for normal ambient use.

**Protective Gloves:**

Recommended when handling hot product.

**Eye Protection:**

Safety glasses or face shield.

**Work/Hygienic Practices:**

Maintain good personal hygiene as standard good work practice.

**Other protective equipment:**

Use impermeable clothing whenever possible to prevent skin contact.

---

## SECTION 9 – REGULATORY INFORMATION

---

**Federal Requirements****SARA TITLE III SECTION 313**

Not applicable based on article exemption

**PROPOSITION 65:**

**WARNING:** Substances known to the state of California to cause cancer: None  
Substances known to the state of California to birth defects or other reproductive harm: None

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Fibre Glast Development Corporation. The data on this sheet relates only to the specific material designated herein. Fibre Glast Developments Corporation assumes no legal responsibility for use or reliance upon these data.

---

**USER'S RESPONSIBILITY**

---

This bulletin cannot cover all possible situations which the user may experience during processing. Each aspect of your operation should be examined to determine if, or where, additional precautions may be necessary. All health and safety information contained in this bulletin should be provided to your employees or customers. It is your responsibility to use this information to develop appropriate work practice guidelines and employee instructional programs for your operation.

---

**SECTION 17 - COMMENTS**

---

The information accumulated herein is believed to be accurate but is not warranted to be, whether originating with Fibre Glast Developments Corporation or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.